



EP341

Product name
Earth Positive® Sweat Shorts

Fibres composition / Yarn type
100% GOTS Organic Cotton Compact Spun

Fabric type / Weight
3-ply french terry brushed 300 g/m²

Commodity code **Origin**
6112 1100 00 India

Available sizes
XS S M L XL 2XL

Certifications

Available colours

Sueded Black
SUBL

Sueded Black Heather
SUBLHE

Sueded Light Blue Heather
SULBHE

Sueded Light Heather
SULHE

Sueded Light Beige
SUSA

Sueded Navy
SUNA

Size spec

Size	Width (A)		Length (B)	
	cm	inch	cm	inch
XS	34	13½	52	20½
S	37	14½	55	21½
M	40	15¾	58	22¾
L	43	17	59	23¼
XL	46	18	60	23½
2XL	49	19¼	60	23½



Discharge printing suitability

Important: This guide serves as a general reference, and results may vary. We strongly recommend testing prior to production.

Sueded colours

		Very Good	Moderate	Not Suitable
	Sueded Black SUBL	✓		
	Sueded Black Heather SUBLHE		✓	
	Sueded Light Blue Heather SULBHE		✓	
	Sueded Light Heather SULHE		✓	
	Sueded Light Beige SUSA	✓		
	Sueded Navy SUNA	✓		



Printing Guide

Print type	Print type	Printing suitability 0 = Not Suitable, 1 = Poor, 2 = Moderate, 3 = Good, 4 = Very Good, 5 = Excellent	Printing recommendations
Fleece 100% Organic Cotton Sueded Colours	Screen print	★★★★★	Follow manufacturer's recommendations for printing and curing settings.
	Discharge	★★★★★	The results may vary from one colour to another. Refer to our discharge printing recommendations on the following page.
	Transfer (Sticker)	★★★★☆	Follow manufacturer's recommendations for curing settings.
	Direct to garment	★★★★☆	Follow manufacturer's recommendations for printing and curing settings.
	Embroidery	★★★★★	Direct embroidery, stitched patch, labels

***Maximum heat recommendation for back neck label** Fusing 180°C / 3-6 sec, 6 psi
Curing 180°C / 1 min

Print type	Print type	Printing suitability 0 = Not Suitable, 1 = Poor, 2 = Moderate, 3 = Good, 4 = Very Good, 5 = Excellent	Printing recommendations
Fleece 100% Organic Cotton Heather Colours	Screen print	★★★★★	Follow manufacturer's recommendations for printing and curing settings.
	Discharge	★★★★☆	The results may vary from one colour to another. Refer to our discharge printing recommendations on the following page.
	Transfer (Sticker)	★★★★☆	Follow manufacturer's recommendations for curing settings.
	Direct to garment	★★★★☆	Follow manufacturer's recommendations for printing and curing settings.
	Embroidery	★★★★★	Direct embroidery, stitched patch, labels

***Maximum heat recommendation for back neck label** Fusing 180°C / 3-6 sec, 6 psi
Curing 180°C / 1 min