



EP026

Product name
Earth Positive® Women's Premium Boxy T-shirt

Fibre composition / Yarn type
100% GOTS Organic CottonCompact Spun

Fabric type / Weight
Jersey 5.5 oz/yd² 185 g/m²

Commodity code
6109 1000 10

Origin
India

Available sizes
S M L

Certifications



Available colours




Black
BL



White
WH



Stone Washed Black
SBL



Size spec

Size	Width (A)		Length (B)	
	cm	inch	cm	inch
S	51	20	50	19¾
M	54	21¼	51.5	20¼
L	57	22½	53	20¾



Discharge printing suitability

Important: This guide serves as a general reference, and results may vary. We strongly recommend testing prior to production.

Core colours		Stone washed		
		Very Good	Moderate	Not Suitable
<div><div></div><div>Black BL</div></div>	<div><div>✓</div></div>			
<div><div></div><div>White WH</div></div>	<div><div>✓</div></div>			

		Very Good	Moderate	Not Suitable
<div><div></div><div>Stone Washed Black SBL</div></div>	<div><div></div></div>	<div><div>✓</div></div>		



Printing Guide

Print type	Print type	Printing suitability 0 = Not Suitable, 1 = Poor, 2 = Moderate, 3 = Good, 4 = Very Good, 5 = Excellent	Printing recommendations
Jersey 100% Organic Cotton Solid Colours (excluding RFD colours)	Screen print	★★★★★★	Follow manufacturer's recommendations for printing and curing settings.
	Discharge	★★★★★★	The results may vary from one colour to another. Refer to our discharge printing recommendations on the following page.
	Transfer (Sticker)	★★★★★☆	Follow manufacturer's recommendations for curing settings.
	Direct to garment	★★★★★★	Follow manufacturer's recommendations for printing and curing settings.
	Embroidery	★★★★★★	Direct embroidery, stitched patch, labels

***Maximum heat recommendation for back neck label** Fusing 180°C / 3-6 sec, 6 psi
Curing 180°C / 1 min

Print type	Print type	Printing suitability 0 = Not Suitable, 1 = Poor, 2 = Moderate, 3 = Good, 4 = Very Good, 5 = Excellent	Printing recommendations
Jersey 100% Organic Cotton Stone Washed, Acid Washed & Tie Dye Colours	Screen print	★★★★★★	Follow manufacturer's recommendations for printing and curing settings.
	Discharge	★★★★★★	The results may vary from one colour to another. Refer to our discharge printing recommendations on the following page.
	Transfer (Sticker)	★★★★★☆	Follow manufacturer's recommendations for curing settings.
	Direct to garment	★★★★★☆	Follow manufacturer's recommendations for printing and curing settings.
	Embroidery	★★★★★★	Direct embroidery, stitched patch, labels

***Maximum heat recommendation for back neck label** Fusing 180°C / 3-6 sec, 6 psi
Curing 180°C / 1 min